

NISSAN INTERSTAR
E-BROCHURE





The Interstar range is both extensive and practical and is available in two grades to ensure there is a version to suit your needs. As the demands of every business are different, we also offer a range of options for alternative load carrying, extra comfort and more convenience.

E

CARGO AREA ACCESSIBILITY

- Unglazed 180° opening rear doors
- Unglazed left sliding door
- Side and rear door activated loading lamps
- Floor mounted lashing rings

SAFETY AND SECURITY

- Driver airbag
- 3-point seatbelts (x2)
- Seatbelt pretensioners
- High mounted rear stop light
- 1/3 tubular bulkhead behind driver
- Immobiliser and alarm
- Remote central locking
- Automatic door locking

COMFORT AND CONVENIENCE

- Single CD player with steering wheel controls
- 3-way adjustable driver seat
- Power assisted steering
- Twin passenger seat bench

OPTIONS

- Metallic paint



SE

ADDITIONAL TO E

FEATURES ON SE GRADE

- Full steel bulkhead
- ABS with Emergency Brake Assist
- Rear Parking Proximity Sensor
- Driver's armrest
- Power windows
- Power and heated mirrors
- Trip computer

OPTIONS

- Metallic paint
- Right sliding door unglazed
- Power take off
- Passenger airbag
- 270 rear doors (unglazed) on L2 / L3
- Satellite navigation
- Digital Tachograph
- Air conditioning and front fog lights

OPTION PACKS

- Comfort Pack
 - Air conditioning
 - 3 Button key allowing opening / locking of selected doors
 - Intelligent wipers
 - Friendly lighting
 - One-touch power windows
- Glazed Rear Doors Pack
 - Glazed rear doors 180° opening
 - Glazed bulkhead
 - Heated rear window
- Glazing Pack
 - Glazed rear doors 180° opening
 - Driver tubular bulkhead
 - Heated rear window
 - Twin glazed side sliding doors
 - Adjustable single passenger seat

SE CREW VAN

ADDITIONAL TO SE VAN

FEATURES ON SE GRADE

- 3 Rear seats with integral bulkhead
- Twin glazed side doors (Right hand door with opening window)
- Glazed rear doors

OPTIONS

- Metallic paint

SE 16 SEAT MINIBUS

ADDITIONAL TO SE VAN

FEATURES ON SE GRADE

- Full glazing
- Sliding left hand door with opening window
- 16 Seats including driver seat
- Rear step
- Retractable side step
- Fire extinguishers x2
- Digital Tachograph
- Mandatory Speed limiter - 62mph
- First aid kit
- Bulkhead deleted
- Rear parking proximity sensor

OPTIONS

- Air conditioning front and rear
- Additional cabin heating
- Satellite navigation
- Overhead luggage rack in cabin

Interstar Vans

MODEL		INTERSTAR										
Wheelbase	Short			Medium			Long					
GVW	2.8		3.3	3.3	3.5		3.5					
Roof height	Low			Mid			Mid	High				
Engine	2.5 dCi 100		2.5 dCi 100	2.5 dCi 100	2.5 dCi 100	2.5 dCi 120	2.5 dCi 120	2.5 dCi 120		2.5 dCi 150		
Transmission	Manual		Manual	Manual	Manual	Man	Auto	Manual	Man	Auto	Man	Auto
ENGINE												
No. of Cylinders	4											
Valves per Cylinder	4											
Engine capacity	cm ³	2464										
Bore x Stroke	mm	89 x 99										
Maximum Engine Power	hp	100	100	100		120		150	120	150		
	rpm	3500										
Maximum Torque	Nm	260	260	260		300		320	300	320		
	rpm	1500										
Compression Ratio	17.8:1											
Emissions Standards	Euro IV											
Fuel Type	Diesel											
Fuel Supply	Direct diesel injection + Common Rail											
Battery	V/Ah	12V/95 Ah										
Alternator	A	150										
DRIVE TRAIN												
Number of speeds	6											
Gear Ratio	1st	6.89	6.76	6.76	6.89							
	2nd	12.88	12.64	12.64	12.88							
	3rd	20.76	20.37	20.37	20.76							
	4th	29.52	28.97	28.97	29.52							
	5th	38.09	37.36	37.36	38.09							
	6th	45.12	44.27	44.27	45.12		48.34	45.12	48.34			
Driven wheels	FWD											
CHASSIS												
Suspension	Front	Independent double wishbone with coil spring, and stabilizer bar										
	Rear	Variable rate leaf springs with telescopic dampers										
Braking system	Front: Ventilated discs Rear: Discs (Diameter 305mm)											
Wheel Size			6J16	16 x 6J								
Tyre Size	195/65R16		215/65R16	215/65R16	225/65R16	225/65R16						
PERFORMANCE												
Maximum Speed	km/h	140	147	140	138		144		140	147	144	140
	mph	87	91	87	86		89		87	91	89	87
Min. Turning Circle (Wall to Wall)	m	12.48			14.11			15.68				
Min. Turning Circle (Kerb to Kerb)	m	12.07			13.75			15.20				

MODEL		INTERSTAR											
Wheelbase		Short			Medium			Long					
GVW		2.8	3.3	3.3	3.5		3.5						
Roof height		Low			Mid			Mid		High			
Engine		2.5 dCi 100	2.5 dCi 100	2.5 dCi 100	2.5 dCi 100	2.5 dCi 120	2.5 dCi 120		2.5 dCi 120	2.5 dCi 150			
Transmission		Manual	Manual	Manual	Manual	Man	Auto	Manual		Man	Auto	Man	Auto
WEIGHTS													
Gross Vehicle Weight	Kg	2800	3300	3300	3500								
Kerb weight	Kg	1815	1818	1887	1894	1902	1937		1964	1972	1979	1986	
Maximum Payload	Kg	985	1482	1413	1606	1598	1563		1536	1528	1521	1514	
Gross Axle Weight	Kg	1550	1750	1750	1850								
	Kg	1600	1900	1900	2060								
Max. Trailer Cap.	Braked	Kg	2000										
	Unbraked	Kg	750										
OVERALL DIMENSIONS													
Length	mm	4899			5399			5899					
Width with mirrors	mm	2361											
Width without mirrors	mm	1990											
Height (unladen)	mm	2232	2232	2486		2484		2716					
Wheelbase	mm	3078	3078	3578			4078						
Overhang	Front	mm	862										
	Rear	mm	959										
Track	Front	mm	1740										
	Rear	mm	1725										
Ground Clearance (unladen)	mm	150											
CARGO AREA DIMENSIONS													
Maximum Length	mm	2714			3214			3714					
Maximum Width	mm	1764											
Maximum Height	mm	1670			1912				2146				
Minimum Width between the Wheelarches	mm	1282											
Max. Load platform height	mm	543			540		537		536				
Cargo Volume	m ³	8.0			10.8			12.6		13.9			
Side Door	Width	mm	1099										
	Height	mm	1555	1800									
Back Door	Width	mm	1515										
	Height	mm	1632	1874									
FUEL TANK													
Fuel tank capacity	L	100											

Interstar Passenger Vehicles

MODEL		INTERSTAR CREW VAN		INTERSTAR 16 SEAT MINIBUS	
Wheelbase		Medium	Long	Long	
GVW		3.3	3.5	3.9	
Roof height		Mid	Mid	Mid	Mid
Engine		2.5dCi 100	2.5dCi 120	2.5dCi 120	2.5dCi 120
Transmission		Manual	Manual	Manual	Semi Auto
ENGINE					
No. of Cylinders		4		4	
Valves per Cylinder		4		4	
Engine Capacity	cm ³	2464		2464	
Bore x Stroke	mm	89x99		89x99	
Maximum Engine Power	hp	100	120	120	
	rpm	3500		3500	
Maximum Torque	Nm	260		300	
	rpm	1500		1500	
Compression Ratio		17.8:1		17.8:1	
Emmissions Standards		Euro IV		Euro IV	
Fuel Type		Diesel		Diesel	
Fuel Supply		Direct diesel injection + common rail		Direct diesel injection + common rail	
Battery	V/ah	12V/95 Ah		12V/95 Ah	
Alternator	A	150		150	
DRIVE TRAIN					
Number of Speeds		6		6	
Gear ratio	1st	6.76	6.89	6.89	6.89
	2nd	12.64	12.88	12.88	12.88
	3rd	20.37	20.76	20.76	20.76
	4th	28.97	29.52	29.52	29.52
	5th	37.36	38.09	38.09	38.09
	6th	44.27	45.12	45.12	45.12
Driven wheels		FWD		FWD	
CHASSIS					
Suspension	Front	Independent double wishbone with coil spring and stabilizer bar		Independent double wishbone with coil spring and stabilizer bar	
	Rear	Variable rate leaf springs with telescopic dampers		Variable rate leaf springs with telescopic dampers	
Braking system		Front:Ventilated Discs - Diameter: 305 mm Rear: Discs - Diameter: 305 mm		Front:Ventilated Discs - Diameter: 305 mm Rear: Discs - Diameter: 305 mm	
Wheel size		6 J16		6 J16	
Tyre size		215/65R16		225/65R16	225/65R16

MODEL		INTERSTAR CREW VAN		INTERSTAR 16 SEAT MINIBUS	
Wheelbase		Medium	Long	Long	
GVW		3.5	3.5	3.9	
Roof height		Mid	Mid	Mid	Mid
Engine		2.5dCi 100	2.5dCi 120	2.5dCi 120	2.5dCi 120
Transmission		Manual	Manual	Manual	Semi Auto
PERFORMANCE					
Maximum Speed	km/h	138	144	144	
	mph	86	89	89	
Min. Turning Circle (Wall to Wall)	m	14.11	15.68	15.68	
Min. Turning Circle (Kerb to Kerb)	m	13.75	15.20	15.20	
WEIGHTS					
Gross Vehicle Weight	kg	3500	3500	3900	
Kerb Weight	kg	2009	2052	2383	2390
Maximum Payload	kg	1491	1448	1500	
Gross Axle	Front	kg	1750	1850	
	Rear	kg	1900	2060	
Max. Trailer Cap.	kg	2000		-	
	kg	750		-	
OVERALL DIMENSIONS					
Length	mm	5399	5899	5899	
Width with mirrors	mm	2361		2361	
Width without mirrors	mm	1990		1990	
Height (unladen)	mm	2486		2456	
Wheelbase	mm	3578	4078	4078	
Overhang	Front	mm	862		862
	Rear	mm	959		959
	TrackFront	mm	1740		1740
	Rear	mm	1725		1725
Ground Clearance (unladen)	mm	150		150	
CARGO AREA DIMENSIONS					
Maximum Length	mm	2160 (2730)*	2660 (3230)*	788	
Maximum Width	mm	1764		-	
Maximum Height	mm	1912		1912	
Minimum Width between the Wheelarches	mm	1282		1294	
Max. Load platform height	mm	540		503	
Cargo Volume	m ³	6.5	8.9	0.5	
Side door	Width	mm	1099		1099
	Height	mm	1800		1806
Back door	Width	mm	1515		1423
	Height	mm	1874		1873
FUEL TANK					
Fuel tank capacity	L	100		100	

* Including aperture under rear seat.

INTERSTAR VAN PRICE LIST



Wheelbase	Roof	Engine	Power	GVW (kg)	Grade	Payload (kg)	Transmission	Basic Delivered	VED + 1st Reg	Basic On The Road
Medium	Mid	2.5 dCi	100HP	3,300	SE	1,413	6 manual	21,095	255	21,350
	Mid	2.5 dCi	100HP	3,500	SE	1,606	6 manual	21,950	255	22,205
	Mid	2.5 dCi	120HP	3,500	SE	1,606	6 manual	22,950	255	23,205
Long	Mid	2.5 dCi	120HP	3,500	SE	1,563	6 manual	24,250	255	24,505
	High	2.5 dCi	120HP	3,500	SE	1,536	6 manual	24,950	255	25,205

The Basic Delivered price excludes VAT but includes delivery to the dealership and number plates. The Basic On The Road price excludes VAT but includes delivery to the dealership, number plates, 12 months Vehicle Excise Duty (£200) and Government First Registration Fee of £55.



Cabstar



Primastar



Kubistar

SHIFT_ is an English word from a Japanese car company that best embraces our values and the mission of this corporation. No matter where you are in the world, SHIFT_ is the way we express who we are, how we work and what we are trying to accomplish.

Everything we touch, we SHIFT_ And everything we SHIFT_ we try to make better and uniquely Nissan.

Visit our websites at:

www.nissan.co.uk

www.nissan-lcv.co.uk

Dealer stamp:



SHIFT_business

We take all our environmental responsibilities very seriously - innovation comes today with a deep respect for the environment. Our engines are now much more unobtrusive and their emissions have been considerably reduced. All our vehicles are designed with recycling in mind and are on target to reach 95% recyclability. This brochure is for general guidance only and its contents do not in any way constitute an offer or representation from Nissan. Every effort has been made to ensure that the content of this publication is correct at the time of going to print. This brochure has been produced featuring prototype vehicles exhibited at motor shows. In accordance with the company's policy of continuously improving its products, Nissan Europe reserves the right to change at any time the specifications and the vehicles described and shown in this publication. Nissan dealers will be informed of any such modifications as quickly as possible. Please check with your Nissan dealer to receive the most up-to-date information. Because of the limitations of the printing processes used, the colours shown in this brochure may differ slightly from the actual colours of the paint and interior trim materials used. All rights reserved. Reproduction in whole or part of this brochure without the written consent of Nissan Europe is forbidden. Benefits and services are provided by RAC Motoring Services and/or RAC Insurance Limited. RAC Motoring Services (Company No. 01424399, Head Office: 8 Surrey Street, Norwich, NR1 3NG) in respect of insurance mediation activities only and RAC Insurance Limited (Company No. 2355834, Head Office: 8 Surrey Street, Norwich, NR1 3NG) are authorised and regulated by the Financial Services Authority within the jurisdiction of the Financial Ombudsman Service and the Financial Services Compensation Scheme. Calls may be monitored and/or recorded.